



5 Keunggulan Seapro Luxfer Scuba Tank :

- ☑ Menggunakan bahan aluminium 6061-T6 yang dikembangkan oleh Luxfer metallurgists.
- ☑ Silinder tekanan tinggi yang dioptimalkan untuk meningkatkan daya tahan.
- ☑ Tangguh dan tahan pecah / retak, walaupun di bawah beban tekanan tinggi dalam jangka waktu lama.
- ☑ Anti karat (Superior corrosion - resistance).
- ☑ Kinerja yang dapat diandalkan dalam menghadapi berbagai lingkungan bawah laut yang beresiko.

When choosing a scuba tank, consider 'The Seapro Luxfer Scuba Tank'

Seapro uses high-pressure cylinders from luxfer L6X^o, 6061 aluminum alloy that is ideal for scuba tanks, with resistant blend specifically to provide excellent performance in the most demanding high - pressure applications. L6X^o alloy is optimized to improve durability, fracture toughness and resistance to tearing and cracking, even under high - pressure loads over long periods.

Seapro luxfer scuba tank offers the 4,500-psi, the world's highest-pressure scuba tank. Because this high- tech tank provides more time underwater, it's especially well-suited for cave diving, wreck diving and other extreme underwater activities.



Specification :

Part Number	Service Pressure		Air Capacity		Outside Diameter		Overall Length		Empty Weight		Internal Volume		Water Weight		Salt Water Buoyancy					
	psi	bar	cu ft	liters	in	mm	in	mm	lbs	kgs	cu in	liters	lbs	kgs	Full	Half		Empty		
															lbs	kgs	lbs	kgs	lbs	kgs
S006	3000	207	6.1	172.8	3.2	81.4	11.1	282.6	2.5	1.2	54	0.9	1.9	0.9	-1.4	-0.6	-1.1	-0.5	-0.9	-0.4
S13S	3000	207	13.2	373.8	4.4	111.1	13.1	333.4	6.0	2.7	116	1.9	4.2	1.9	-1.7	-0.8	-1.2	-0.6	-0.7	-0.3
S014	2015	139	13.7	388.0	4.4	111.1	16.2	411.1	4.9	2.2	172	2.8	6.2	2.8	0.8	0.4	1.3	0.6	1.8	0.8
S019	3000	207	19.9	563.6	4.4	111.1	18.6	471.4	8.2	3.7	175	2.9	6.3	2.9	-1.4	-0.6	-0.6	-0.3	0.1	0.1
S030	3000	207	30.0	849.6	4.4	123.8	21.9	555.0	11.6	5.3	263	4.3	9.5	4.3	-1.0	-0.5	0.1	0.1	1.2	0.6
S040	3000	207	40.0	1132.8	5.3	133.4	24.6	628.7	15.3	6.9	350	5.7	12.6	5.7	-0.7	-0.3	0.8	0.4	2.3	1.0
S050	3000	207	48.4	1370.7	6.9	175.0	19.0	482.6	21.2	9.6	424	6.9	15.3	6.9	-2.3	-1.0	-0.5	-0.2	1.4	0.6
S063	3000	207	63.0	1784.4	7.3	184.2	21.9	555.0	26.7	12.1	552	9.0	19.9	9.0	-2.2	-1.0	0.2	0.1	2.6	1.2
S072	3000	207	69.6	1971.1	6.9	175.0	26.0	660.4	28.5	12.9	610	10.0	22.0	10.0	-1.4	-0.6	1.2	0.6	3.8	1.7
S080	3000	207	77.4	2192.0	7.3	184.2	26.1	661.9	31.4	14.2	678	11.1	24.5	11.1	-1.4	-0.6	1.5	0.7	4.4	2.0

Made in USA